

## Aerohive AP245 802.11ac Dual Radio Access Point

High performance, general purpose 802.11ac Wave2 Dual-Radio 3x3:3 access point with external antennas.

AP245X enterprise access point combines high-performance 802.11ac Wave2 with the simplicity of Aerohive's distributed, cooperative architecture. This power optimised access point line uniquely incorporates next generation 802.11ac, integrated BLE radio for iBeacon and other beacon applications and a standard USB port for variety of IoT applications. AP245X smoothly integrates into your existing 802.3af or 802.3at power and network infrastructure.

The AP245X provides dual concurrent 2.4Ghz 3x3, 3 stream MIMO and 5 GHz 3x3, 3 stream MU-MIMO radios. This access point has an extended operating temperature range and external antenna connectors. AP245X is a perfect fit for challenging environments where deployments require specialized antennas or higher temperature ranges.

### Key Benefits

- Enterprise software features including RADIUS, DHCP server, location services and spectrum analysis are combined with hardware assisted security and zero-touch deployment.
- Upgrading your network to 802.11ac Wave 2 does not require you to upgrade your existing PoE infrastructure. Our advancements in energy efficiency allow the AP245X full 3-stream, 2.4GHz and 5 GHz 802.11ac performance while using existing 802.3af PoE infrastructure.
- Integrated BLE ( Bluetooth Low-Energy) radio enables mobile engagement services that can be based on ambient data, micro-location or orientation.
- A TPM chip (Trusted Platform Module) provides hardware-based key and configuration encryption for added security.
- Application Visibility and Control functionality, including reporting, stateful firewall, and powerful Aerohive Quality of Service (QoS) on the access point
- Managed from public or private cloud -based HiveManager NG platform.



### Features

- Wave 2 802.11ac Access Point with MU-MIMO capability
- Extended operation temperature range ( 0 to 50 degrees Celsius)
- Automatic or dedicated mesh backup
- Built-in Bluetooth Low Energy for iBeacon and other beacon technologies
- IOT readiness with USB port for other wireless technologies to connect seamlessly

### Security Features

- Trusted Platform Module (TPM)– Hardware-based key storage and encryption
- Wireless privacy & authentication Wi-Fi CERTIFIED WPA and WPA2, private PSK
- Granular user profile-based management defines traffic and security policies for groups of users or individual users
- Encryption: AES/CCMP, TKIP, and RC4 (WEP only)
- Classifying, Marking and Policing–WMM (802.11e) for wireless, 802.1p and/or DiffServ for wired
- WMM Certified
- WMM Power Save (U-APSD) Certified

### Advanced Features

- Integrated application visibility and control (AVC)
- Advanced Automatic Channel Selection Protocol (ACSP) for optimum radio performance.
- On-device RADIUS Server with directory integration support (max 256 concurrent authentications), Captive Web Portal, DHCP server (max 512 DHCP clients per AP), and spectrum analysis

## AP245X Product Specifications

### Radio Specifications—802.11a

- 5.150–5.850 GHz Operating Frequency
- Orthogonal Frequency Division Multiplexing (OFDM) Modulation
- Rates (Mbps): 54, 48, 36, 24, 18, 12, 9, 6 w/ auto fallback

### Radio Specifications—802.11b

- 2.4–2.5GHz Operating Frequency
- Direct-Sequence Spread-Spectrum (DSSS) Modulation
- Rates (Mbps): 11, 5.5, 2, 1 w/auto fallback

### Radio Specifications—802.11g

- 2.4–2.5 GHz Operating Frequency
- Orthogonal Frequency Division Multiplexing (OFDM) Modulation

### Modulation

- 20 dBm (100 mW) Transmit Power
- Rates (Mbps): 54, 48, 36, 24, 18, 12, 9, 6 w/ auto fallback

### Radio Specifications—802.11n

- 2.4–2.5 GHz & 5.150–5.850 GHz Operating Frequency
- 802.11n Modulation
- Rates (Mbps): MCS0–MCS23 (6.5Mbps – 450Mbps)
- 3x3:3 Stream Multiple-In, Multiple-Out (MIMO) Radio
- HT20 High-Throughput (HT) Support (for both 2.4 GHz and 5 GHz)
- A-MPDU and A-MSDU Frame Aggregation

### Radio Specifications—802.11ac

- 5.150–5.850 GHz Operating Frequency
- 802.11ac Modulation (256-QAM)
- Rates (Mbps): MCS0–MCS9 (6.5Mbps – 1300Mbps), NSS = 1-3.
- 3x3:3 Stream Multiple-In, Multiple-Out (MIMO) Radio
- VHT20/VHT40/VHT80 support

### Included Mounting Options

- Wall Mount
- Ceiling Tile flush 15/16" and Wall Mount locking accessory

### Included with AP Mounting

- Desktop
- Ceiling Tile Recessed 15/16", 3/8", 9/16" sold as an accessory
- Ceiling Tile flush 3/8", 9/16" sold as an accessory
- Suspend Mount sold as an accessory
- Plenum Mount sold as an accessory
- Silhouette and Interlude sold as an accessory

### Antennas

- 3x RP-SMA connector 2.4 GHz
- 3x RP-SMA connector 5 GHz
- 1x BLE internal antenna

### Interfaces

- Two Autosensing 10/100/1000 Base-T Ethernet ports. PoE (Power over Ethernet 802.3af) capability on one of the ports
- RJ-45 console port

### Physical

- WxDxH: 7.25" x 7.25" by 1 7/8" tall (plus .25" for the mounting hardware) – so 2.12" (5.4 cm) high total

### Environmental

- Operating: 0 to +50°C, Storage: -40 to +70°C
- Humidity: 95%

### Environmental Compliance

- UL2043

### Power Specifications

- IEEE 802.3af PoE Power: Full 3x3:3 802.11ac MU-MIMO performance and BLE. No USB port, no 2nd Ethernet port.
- IEEE 802.3at PoE Power: full set of features (all of the above plus USB port and 2nd Ethernet port).
- 802.3af Power over Ethernet (PoE) capable Gigabit Ethernet port (RJ-45 power input pins: Wires 4,5,7,8 or 1,2,3,6)
- 802.3at Power over Ethernet injector


Aerohive Power Table

| 2.4 GHz  | Data Rate            | Power dBm |
|----------|----------------------|-----------|
| 11b      | 1,2,5,11             | 17/20     |
| 11g      | 54 Mbps              | 15/17     |
|          | 48 Mbps              | 16/18     |
|          | 36 Mbps              | 17/19     |
|          | 6 Mbps               | 17/19     |
| 11n HT20 | MCS7,15,23           | 15/17     |
|          | MCS6,14,22           | 16/18     |
|          | MCS5,13,21           | 17/19     |
|          | MCS0,12,3,4          | 17/19     |
|          | MCS8,9,10,11,12      |           |
|          | MCS16,17,18,19,20    |           |
| 5 GHz    | Data Rate            | Power dBm |
| 11a      | 54 Mbps              | 15/17     |
|          | 48 Mbps              | 16/18     |
|          | 36 Mbps              | 17/19     |
|          | 6 Mbps               | 17/19     |
| 11n HT20 | MCS7,15,23           | 15/17     |
|          | MCS6,14,22           | 16/18     |
|          | MCS13,21             | 17/19     |
|          | MCS0,2,3,4,8,9,10,11 | 17/19     |
|          | MCS12,16,17,18,19,20 |           |
| 11n HT40 | MCS7,15,23           | 15/17     |
|          | MCS6,14,22           | 16/18     |
|          | MCS5,13,21           | 17/19     |
|          | MCS0,12,3,4,8        | 17/19     |
|          | MCS9,10,11,12,16     |           |
|          | MCS17,18,19,20       |           |
| 11ac VHT | 256QAM@3/4 Code Rate | 12/14     |
|          | 256QAM@5/6 Code Rate | 11/13     |


Aerohive Power Table

| 2.4 GHz   | Data Rate      | Sensitivity |
|-----------|----------------|-------------|
| 11b       | 1 Mbps         | -100        |
|           | 11 Mbps        | -93         |
| 11g       | 6 Mbps         | -95         |
|           | 36 Mbps        | -86         |
|           | 48 Mbps        | -82         |
|           | 54 Mbps        | -80         |
| 11n HT20  | MCS0, 8, 16    | -95         |
|           | MCS5,13, 21    | -81         |
|           | MCS6,14, 22    | -79         |
|           | MCS7, 15, 23   | -77         |
| 5 GHz     | Data Rate      | Sensitivity |
| 11a       | 6 Mbps         | -95         |
|           | 36 Mbps        | -86         |
|           | 48 Mbps        | -81         |
|           | 54 Mbps        | -80         |
| 11n HT20  | MCS0, 8, 16    | -91         |
|           | MCS5, 13, 21   | -78         |
|           | MCS6, 14, 22   | -76         |
|           | MCS7, 15, 23   | -74         |
| 11n HT40  | MCS0, 8, 16    | -88         |
|           | MCS5, 13, 21   | -75         |
|           | MCS6, 14, 22   | -73         |
|           | MCS0,7, 15, 23 | -71         |
| 11ac HT20 | Code Rate 3/4  | -65         |
|           | Code Rate 5/6  | -63         |
| 11ac HT40 | Code Rate 3/4  | -62         |
|           | Code Rate 5/6  | -60         |
| 11ac HT80 | Code Rate 3/4  | -59         |
|           | Code Rate 5/6  | -57         |


Radiation Patterns




Vertical  
2GHz Dual-band



Horizontal  
2GHz Dual-band



Vertical  
5GHz Dual-band



Horizontal  
5GHz Dual-band

Contact Krome today on 01932 232345 to learn how your organisation can benefit from an Aerohive wireless LAN architecture.

## Krome Wireless Deployment Planning Service

**We can deliver you a Wireless solution that caters for your individual business, and specific site requirements.**

To create a WLAN solution that works effectively, there are several considerations that have to be made, the multiple client device and application types that are required to perform over the wireless infrastructure is just the start, in addition to that you need to add the speed and complexity of 802.11n, the variety of potentially high demanding applications or high-density environments and the security risks, with so many factors to consider tricky deployment scenarios can easily arise, causing unexpected challenges to the success of your Wireless deployment.

Krome offer a comprehensive wireless deployment planning service to fully assess and effectively plan the solution prior to installation.



### Assessing Your Requirements

To get started with your WLAN installation, Krome will examine the requirements of your implementation, including departmental, individual user, site, and application requirements, gaining a basic overview of what your Wireless network will need to support. We will identify mission critical applications, paying special attention to those that generate high levels of traffic and those requiring deterministic behavior. Once we have identified such applications we can then evaluate the expected service levels.

### Effective Planning

Whether you are upgrading from an existing WLAN or planning a completely new greenfields site Krome can fully evaluate and plan the deployment by using a WLAN planning tool and building floor plans. The planning tool is designed to help scope and plan a WiFi Deployment to determine the number of APs required to achieve an intended coverage, AP placement and data rates. This tool calculates the loss in signal strength as it passes through open air and various materials to show predicted coverage.

### Upgrading from Existing Wi-Fi

If you are upgrading your existing WLAN, you already have plenty of data about how your current network is performing. Krome will initially perform a quick site survey with the existing access points in place, evaluating the current coverage, capacity, and type of APs (access points). Using the survey information allows us to make informed decisions about your new implementation. Krome will provide a report on how to achieve optimal results and performance with your new deployment, along with the quickest and most effective way to migrate systems.

### New WLAN Deployment

In a new, or greenfield, WLAN deployment; when you do not have the benefit of an existing network for testing and analysis, the planning stage is more complex. Determining the scope of your WLAN deployment will have a major impact on capacity and coverage. Krome will evaluate users, applications, interference's, devices and performance requirements, along with building plans and site information. Site plans and blueprints are hugely beneficial for planning as we are able to evaluate the building characteristics; location of elevators, load-bearing walls and material of walls. With this information loaded into the planning tool combined with our analysis of your service requirements we are able to comprehensively plan for your deployment.

### Deploying with Confidence

Moving a large enterprise, or even a small one, to a WLAN for the very first time need not be daunting; with proper planning in place, you can prevent poor performance and eliminate unforeseen solution costs. By engaging with highly experienced Wireless deployment partner Krome Technologies to effectively assess and plan your deployment you can be assured that your WLAN solution is a success.

### Find Out More

If you're interested in learning more about Aerohive Networks WLAN solutions or our deployment planning service please do get in touch with one of our Business Managers, we'd love to share our experiences, and help you to plan and deliver your Aerohive WLAN solution.

Telephone: +44 (0) 1932 232345  
Email: [info@krome.co.uk](mailto:info@krome.co.uk)